



FEATURES

- Modular Design.
- System power up to 30W.
- Interchangeable beam.
- Interchangeable anti-glare reflector.
- 5-year guarantee.

Technical Data

Input Voltage/Hz	AC220-240V 50/60Hz
Output Voltage/Current	DC36V/600mA
Power	23.5W
Rated Input Current	0.125A
PF value	>0.9
THD	<7%
Ingress Protection	IP54
Operating Temperature	-10-40°C
Dimmability	Non-dimmable or DALI

LED and Optical Data

LED Brand	Bridgelux COB LED
CRI	Ra>90
SDCM	<3
Beam Angle	15°/24°/36°/60°
Colour temperature	2700K/3000K/4000K
System luminous efficacy up to	106lm/W



Packaging

Box Dimensions	L210 x W210 x H145mm
Box Net Weight	1.2Kg
Box Gross Weight	1.41Kg
Carton Dimensions	L435 x W435 x H460 mm/12 PCS
Carton Net Weight	14.4Kg
Carton Gross Weight	17.72Kg

Model	CCT	Beam Angle	Lumen	Efficacy	CRI R-Value	Life Rating
LS51-25-XX-01	2700K	15°	2141lm	92lm/W	R9=72	25W > 105000H L90 B10
		24°	2050lm	88lm/W	R9=72	25W > 105000H L90 B10
		36°	2151lm	92lm/W	R9=70	25W > 105000H L90 B10
		60°	2137lm	92lm/W	R9=70	25W > 105000H L90 B10
LS51-25-XX-01	3000K	15°	2295lm	101lm/W	R9=74	25W > 105000H L90 B10
		24°	2193lm	96lm/W	R9=74	25W > 105000H L90 B10
		36°	2324lm	101lm/W	R9=72	25W > 105000H L90 B10
		60°	2276lm	99lm/W	R9=73	25W > 105000H L90 B10
LS51-25-XX-01	4000K	15°	2432lm	105lm/W	R9=73	25W > 105000H L90 B10
		24°	2358lm	102lm/W	R9=73	25W > 105000H L90 B10
		36°	2451lm	106lm/W	R9=70	25W > 105000H L90 B10
		60°	2454lm	105lm/W	R9=71	25W > 105000H L90 B10